

# IMAGEMOUSE PLUS SPECIFICATIONS

The ImageMouse® basic unit includes the illuminated base and the ImageMouse® with our highly functional, user friendly, Windows-based Image Capture software. The ImageMouse Plus® also includes the motorized Combo-carriers (which accommodates microfiche, 16mm & 35mm open reel microfilm, or aperture cards). Optional 3M and ANSI cartridge carriers can also be ordered. These units can be ordered with either a 24X/28X or 42X/48X magnification rate lens.

**DIMENSIONS** 8" High x 24.75" Wide x 15" Deep

\* Allow additional 7" for X&Y movement clearance

**WEIGHT** 19.3 lbs.

## VIEWING FUNCTION

**Film Size** 105mm cut microfiche, 16mm and 35mm\* rollfilm

**Film Type** Negative ad positive, diazo and vesicular, original and duplicate

## INTERCHANGEABLE IMAGE CAPTURE UNIT

**Image Size** 42X/48X or 24X/28X reduction range

**Resolution** 1.3 megapixels

## IMAGING SPEED

**View** 150 ms/frame

**Frame Capture** Sub one second

## INTERFACE/POWER

**Interface** Universal Serial Bus (USB) port

**Power** 110V-240V; 50/60 Hz, U.L./C.E.Approved

## OPTIONS

Interchangeable 42X/48X and 24X/28X ImageMouse® capture units. Manual roll carrier. ANSI cartridge carriers can also be ordered. These units can be ordered with either a 24X/28X or 42X/48X magnification rate lens.

## RECOMMENDED PC CONFIGURATIONS

**CPU** Pentium® class, 1 GHz or greater

**RAM** 128 MB or greater

**Video RAM** 64 MB (capable of 1600 x 1200 resolution)

**HDD** 50 MB (Free Space)

**Monitor** 19" UXGA or capable of 1600 x 1200 resolution

**USB Support** Required

## OPERATING SYSTEM

Microsoft®Windows® '98 Second Edition, Windows® NT® 4.0 Server, Windows® ME

\*35mm rollfilm and aperture cards may not be viewed full frame.  
All trademarks are property of their respective owners.